



HW#2 → 3.22, 3.28a, 3.32, 3.37, 3.46, 3.52, 3.70, 3.94

Contact Resistance

3.22 Consider a plane composite wall that is composed of two materials of thermal conductivities $k_A = 0.1 \text{ W/m} \cdot \text{K}$ and $k_B = 0.04 \text{ W/m} \cdot \text{K}$ and thicknesses $L_A = 10 \text{ mm}$ and $L_B = 20 \text{ mm}$. The contact resistance at the interface between the two materials is known to be $0.30 \text{ m}^2 \cdot \text{K/W}$. Material A adjoins a fluid at 200°C for which $h = 10$

$\text{W/m}^2 \cdot \text{K}$, and material B adjoins a fluid at 40°C for which $h = 20 \text{ W/m}^2 \cdot \text{K}$.

- (a) What is the rate of heat transfer through a wall that is 2 m high by 2.5 m wide?
- (b) Sketch the temperature distribution.



HW#2 → 3.22, 3.28a, 3.32, 3.37, 3.46, 3.52, 3.70, 3.94

Alternative Conduction Analysis

3.32 Consider a tube wall of inner and outer radii r_i and r_o , whose temperatures are maintained at T_i and T_o , respectively. The thermal conductivity of the cylinder is temperature dependent and may be represented by an expression of the form $k = k_o(1 + aT)$, where k_o and a are constants. Obtain an expression for the heat transfer per unit length of the tube. What is the thermal resistance of the tube wall?

